

## Hydraulic Pump and Puller (Ram) Matrix

✓ = recommended; ✓ \* = recommended with caution; § = pullers that may be powered by back hoes, loaders, and other field equipment

	PowerTeam 1.25	PowerTeam 5.5	PowerTeam 20 HP	Enerpac 13 HP	Bailey 13 HP	Hi-Flow (WIT) 13	Hi-Flow (WIT) 24	Hi-Flow (WIT) 36
	0.89/0.32 GPM 8,000 psi max	2.0/1.1/0.41 GPM 8,000 psi max	4.8/3.5/1.75 GPM 8,000 psi max	4.3/0.86 GPM 8,000 psi max	4.6 GPM 3000 psi + max	Variable 2-8 GPM 6,000 psi max	Variable 4-8 GPM 7,000 psi max	10/20 GPM 3,000/6,000 psi
C20 4.81 sq.in. 8,000 psi	~	V	~	~			✓ *	
C25 6.28 sq. in 8,000 psi	~	V	~	~		~	✓ *	
<b>X20</b> 4.14 sq. in. 8,000 psi	~	V	~	V				
<b>X30</b> § 9.82 sq. in. 6,000 psi		V	~	V	✓ *	~	✓ *	
<b>V24</b> § 19.24 sq. in. 3,000 psi					✓ *	✓ *	✓ *	
<b>M50</b> § 19.24 sq. in. 5,000 psi							~	v
M100 § 39.27 sq. in. 5,000 psi							~	v